WALL STONE
Technical Data Sheet

PRODUCT SPECIFICATION			
Production identification		Area Spc Wall Tiles	
Surface integrity test		Embossed In Register / Microbevel	
Construction		Vinyl decor with SPC core, scratch coating	
Protection		Ultimate Shield, Scratch, Stain and Wear Resistant - Surface	
Material - Core		Endure Core SPC - Stone Polymer Composite 2000 kg/m3 density	
Surface treatment		UV	
Usage		Residential - Commercial	
Warranty period		Residential 10 years - Commercial 4 years	
Plank Size		305x600	
Joint		Tongue and Groove	
Installation method		Glued	
Total Thickness		4 mm	
Wear layer thickness		0.50 mm	
Length		600 mm.	
Width		305 mm.	
TECNICAL SPECIFICATION			
Thermal resistance		EN 12667	0,0311 M2k/w
Thermal Conductivity		EN 12667	0,296 W/(m.K)
Residual indentation		EN ISO 24343-1	0.01 mm
Micro scratch resistance (class)		TSE CEN/TS 16611	0.1 mm
Emission of formaldehyde		EN 717-1:2004	E1
Resistence to Staining		EN438-2 +A1	Class 34
Light fastness		EN ISO 105-B02:2014	≥6
CE Mark		**13245-2:2008**	**Specification**
Fire behaviour		TS EN 13501-1	Bs3d0
VOC Emissions Class - (French Regulation)			A+
VOC Emission - İndoor Air Comfort Gold			E1
VOC Emission - M1			Pass
AREA FLOORS PRODUCTION : İstanbul / Türkiye			

EUROPAVIMENTI S.R.L.
Via Prà di Risi 5/A – 33080 Zoppola (PN)
Tel. 0434977421 p.iva 01526670938
REG.IMP. C.C.I.A.A. PN n°83727/04